



3DeVOK

Apex Metrology

Freedom to Move, Built to Perform

3DeVOK Airgo Wireless Handle

Seamless control for large-scale objects and field scanning

— Engineered for 3DeVOK MT&MQ 3D Scanners



Outstanding Performance, Seamless&Lag-Free

Wireless transmission up to 70 FPS

Global Wireless Compatibility

Worldwide Wi-Fi with external adapter
Stable, connection with latest tech.

Dual-Battery System for Long-Lasting Power

12,000mAh dual-battery system
Delivers up to 2 hours of nonstop

Detachable Battery for Easy Swaps

Ergonomic Back-clip for Secure Grip

Wired/Wireless Mode Switch with Ease

Airgo Wireless Handle **£239** +VAT

Airgo Wireless Handle Bundle **£445** +VAT

Wireless Handle, 2x Rechargeable Batteries, 2-Slot USB Battery Charger, USB WiFi 6 Adapter & Portable Travel Router



Precisely engineered for seamless use with 3DeVOK MT&MQ 3D scanners, Airgo features an ergonomic back-clip design and incorporates a dual-battery power system alongside global wireless compatibility. It delivers smooth, uninterrupted performance in demanding environments such as large-object scanning and outdoor operations, significantly enhancing the flexibility and efficiency of 3D data acquisition.

3DeVOK Airgo Wireless Handle Technical Specifications	
Model	3DeVOK Airgo
WiFi Protocol (Router&Adapter)	WiFi 6
Frequency (Router&Adapter)	5GHz
Wireless Transmission Rate	Laser - Marker Alignment: Up to 70 FPS Infrared Speckle / Laser Hybrid Alignment (Router mode): Up to 30 FPS Infrared Speckle / Laser Hybrid Alignment (Network adapter mode): Up to 18 FPS
Transmission Distance	10 Meters (Line of sight)
Battery Type	Lithium Battery
Battery Capacity	6000mAh (Each), 2 Batteries Included
Battery Life	2 Hours (with 2 batteries)
Charging Time	4-5 Hours (for 2 batteries)
Charging Device	Battery Charger
Power & Data Interface	Type-C
Phone Mount	Magnetic Type
Battery Cover	Snap-on Design
Power/Scan Button	Mechanical Type
Dimensions	204*138*64mm
Weight	390g (with 2 batteries)
Operating Humidity	10% ~ 90% RH (Non-condensing)
Operating Temperature	0~40°C
Ingress Protection	IP50
Compatible Products	3DeVOK MQ/MT
★Wireless Hardware Version: Supports multiple connection modes, including computer hotspot, 4-meter USB cable (wired), and router-based connection (router sold separately). Modes can be flexibly switched as needed.	
★Wired Transmission Rate:	
- Laser - Marker Alignment: Up to 70 FPS	
- Infrared Speckle & Laser Hybrid Mode: Up to 30 FPS	

